



Date of issue : 05/01/2005
Last. mod. date : 29/08/2008

Product code**01863 COATED 80 RP1011 PLUS GL60Y****Description**

White clay coated, wood free paper for general purpose. Calendered with medium gloss level.

Suitable for different printing systems: letterpress, flexo, offset and gravure. Also for thermal transfer with selected ribbons.

Rubber based hot melt adhesive, with high grammage. High tack and adhesion, particularly on difficult apolar surfaces

Typical applications: high quality multicoloured labels for general and promotional uses.

FACE MATERIAL

Type	Glossy coated paper
Colour and Finish	White
Weight	80 g/m ²
Thickness	65 μ

ADHESIVE

Reference	RP 1011
Type	Hot Melt Permanent
Min. Appl. Temp.	0 °C
Service Temp.	-10 °C/ +70 °C
Shear	High
Tack	High
Ultimate Adhesion	Very high

RELEASE BACKING

Type	Glassine paper
Colour and Finish	Yellow
Weight	62 g/m ²
Thickness	55 μ
Transparency	> 50 %

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.

Ritrama S.p.A.
Ritrama S.p.A. Sassoferrato
Coating Ricofin S.r.l.
Ritrama S.A.
Ritrama Ltd.(UK)
Ritrama Inc. Minneapolis (USA)
Ritrama Inc. Cleveland (USA)

Tel. +39 02 955 459 1
Tel. +39 0732 97061
Tel. +39 02 955 430 1
Tel. +34 93 729 49 98
Tel. +44 161 786 1760
Tel. +1 612 378 2277
Tel. +1 216 851 2300

info@ritrama.it
info@ritrama.it
info@ricofin.it
ritrama@ritrama.es
sales@ritrama.co.uk
info@ritrama.com
info@ritrama.com