



Date of issue : 05/01/2005
Last. mod. date : 21/06/2010

Product code**05591 COVER RP1001 YG60****Description**

Semi-gloss white coated woodfree paper with high opacity.

Printable with letterpress UV, flexo UV, offset UV and gravure.

Rubber based permanent adhesive with high tack and adhesion on difficult and apolar (like PE and PP) substrates.

Blackout/coverall labels.

FACE MATERIAL

Type	Coated paper
Colour and Finish	White
Weight	90 g/m ²
Thickness	72 μ

ADHESIVE

Reference	RP 1001
Type	Rubber permanent
Min. Appl. Temp.	+5°C
Service Temp.	-10°C/+70°C
Shear	Very high
Tack FTM9	16 N/inch ²
FinAdh FTM2	9 N/inch

RELEASE BACKING

Type	One side siliconised Glassine
Colour and Finish	Yellow
Weight	60 g/m ²
Thickness	54 μ
Transparency	>50 %

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.

Ritrama S.p.A.
Ritrama S.p.A. Sassoferrato
Coating Ricofin S.r.l.
Ritrama S.A.
Ritrama Ltd.(UK)
Ritrama Inc. Minneapolis (USA)
Ritrama Inc. Cleveland (USA)

Tel. +39 02 955 459 1
Tel. +39 0732 97061
Tel. +39 02 955 430 1
Tel. +34 93 729 49 98
Tel. +44 161 786 1760
Tel. +1 612 378 2277
Tel. +1 216 851 2300

info@ritrama.it
info@ritrama.it
info@ricofin.it
ritrama@ritrama.es
sales@ritrama.co.uk
info@ritrama.com
info@ritrama.com