



Destructible PE60

Face

White destructible PE film with matt top coating for thermal transfer printing.

	Method	Unit	Target
Weight	ISO 536	g/m ²	60
Thickness	ISO 534	µm	109

Adhesive

Permanent modified acrylic, water based with high initial tack and high final adhesion.
Low resistance to sunlight and low cohesion.

	Method	Unit	Target
Min. Appl. Temperature		°C	+ 5
Service Temperature		°C	- 40 up to + 150

Liner

Super-calendered high density backing paper 73gr/sqm. Constant thickness, good mechanical properties, Suitable for automatic labelling. Good quality for optical scanning.

	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	73
Thickness	ISO 534	µm	63

Application and use

Product with low resistance to delamination, use for making safety labels. If removed, the adhesive layer and part of the film remain on the application surface.

Converting and Printing

Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer.

Packaging

The rolls are sliced according to customer requirements and packed with shrink films. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: CR007521 Date: July 2017

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.