



GLOSS COPPER EMBOSSED

Face

Embossed paper, laminated on the back side with 12 µm clear PET film.

	Method	Unit	Target
Weight	ISO 536	g/m ²	142
Thickness	ISO 534	µm	192

Adhesive

Permanent acrylic adhesive, water based, with high initial tack and high final adhesion. Medium resistance to sunlight and low cohesion. Good adhesion on cold and damp surfaces.

	Method	Unit	Target
Min. Appl. Temperature		°C	+ 10
Service Temperature		°C	- 15 up to + 60

Liner

Super calendared, high density backing paper 73 gr/sqm. Constant thickness, good mechanical properties, suitable for automatic labelling. Good quality for optical scanning

	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	73
Thickness	ISO 534	µm	63

Application and use

Product suitable for the production of labels for the wine and spirits sector. The particular construction makes it resistant to water and humidity. Suitable for labeling on moist and cold surfaces.

Packaging

The rolls are sliced according to customer requirements and packed with shrink films. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: 600310 Date: May 2018

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.