

TECHNICAL DATA SHEET

Platinum Paper Ltd.



TRANSFER AP904 YG60

Face

White woodfree super calendared paper.

Type Calendared paper.
Colour and Finish White

	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	80 ± 10%
Thickness	ISO 534	μ	65 ± 10%

Adhesive

Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP). This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Type Acrylic permanent
Shear Medium

	Method	Unit	Target
Final Adhesive	FTM2	N/inch	11
Tack	FTM9	N/inch	13
Min. appl. temperature		°C	+5
Service temperature		°C	-40 / +100

Liner

Type One side siliconised Glassine.
Colour and finish Yellow

	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	60 ± 10%
Thickness	ISO 534	μm	54 ± 10%
Transparency	DIN 53 147-64	%	>50

Application and use

Bar codes and identification labels.

Converting and Printing

Printable with thermal transfer and also with letterpress UV and flexo UV.

Packaging

The rolls are sliced according to customer requirements and packed with shrink films. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Three years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: 01959 Date: 08/06/11

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.