



---

## Ultradestructible Clear PS

---

### Face

Clear PS film, with low resistance to tearing.

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Weight	ISO 536	g/m <sup>2</sup>	53
Thickness	ISO 534	µm	50

---

### Adhesive

Permanent acrylic, water based with low initial tack and medium final adhesion.  
High resistance to sunlight and high cohesion.

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Min. Appl. Temperature		°C	+ 10
Service Temperature		°C	- 40 up to + 150

### Liner

Super-calendered high density backing paper 78gr/sqm. Constant thickness, good mechanical properties, Suitable for automatic labelling. Good quality for optical scanning.

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Basis Weight	ISO 536	g/m <sup>2</sup>	78
Thickness	ISO 534	µm	67

---

### Application and use

This product is specially designed for security labels. It is extremely fragile face material, tends to break when trying to remove the label.

### Converting and Printing

Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer.

### Packaging

The rolls are sliced according to customer requirements and packed with shrink films. They are delivered on pallets. Product description labels are fixed on rolls.

### Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: CR001021      Date: July 2017

---

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.