



YELLOW FLUORESCENT G PERM

Face

One side fluorescent laminated coated paper.

Type Coated paper.

	Method	Unit	Typical
Basis Weight	ISO 536	GSM	80 ± 4
Thickness	ISO 534	Micron	82 ± 5

Adhesive

General use acrylic permanent adhesive including smooth and slightly rough or curves

	Method	Unit	Typical
Peel adhesion	FINAT1	N/25mm	15.4 to stainless steel (≥12.3)
Loop Tack	FINAT9	N	10 to stainless steel (≥7.8)
Min. appl. temperature		°C	+5
Service temperature		°C	-10 / +70

Liner

Type Honey Glassine liner.

	Method	Unit	Typical
Basis Weight	ISO 536	GSM	62 ± 3
Thickness	ISO 534	Micron	54 ± 4

Application and use

Typical use is for eye catching applications such as warning signs, instructional labels, promotional and point of sales labels. Also suitable for use where there is automatic label registration or dispensing.

Converting and Printing

Graphic print may be applied by a wide variety of techniques, including letterpress, flexographic, screen and litho process. Suitable for Thermal Transfer printing with many printer/ribbon combinations.

Packaging

The rolls are sliced according to customer requirements and packed with shrink films. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: **Date:** 10/10/17

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.