



---

**COATED 80 G ACRYLIC – DEEP FREEZE**

---

**Face**

Gloss coated woodfree paper.

**Type**

Coated

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Substance	ISO 536	g/m <sup>2</sup>	80 ± 4
Thickness	ISO 534	µm	69 ± 4
Tensile Strength MD	ISO 1924-2	kN/m	4,9 -0,5
Paper Gloss 20°	ISO 8254/1	%	66 ± 5

---

**Adhesive**

Acrylic permanent adhesive for frozen and cold surfaces. Should not be exposed to high temperatures and direct UV light.

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Min. Appl. Temperature		°C	- 35
Service Temperature		°C	- 40 up to + 60

**Liner**

Super-calendered yellow translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Basis Weight	ISO 536	g/m <sup>2</sup>	62 ±2
Thickness	ISO 534	µm	52 ±2

---

**Application and use**

High resolution standard gloss label for multicolour printing. Extensively used in the food and beverage industry, logistics, stationery and cosmetics products.

**Converting and Printing**

Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

**Packaging**

The rolls are sliced according to customer requirements and packed with shrink films. They are delivered on pallets. Product description labels are fixed on rolls.

**Shelf Life and Storage Conditions**

One year when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: ACRY 80 CTD DEEP FREEZE      Date: 29/11/2013

---

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.