

# Platinum Paper

## Product: Coated G Removable Acrylic

Face Material	Target	Unit	Method
Substance	80 ± 4	g/m <sup>2</sup>	ISO 536
Thickness	69 ± 5	μ	ISO 534

**Description:** Gloss coated woodfree paper.

Adhesive	Target	Unit	Method
Peel Adhesion (peel 180° 20'/stainless steel)	1.7	n/25mm	FTM 1
Shear (1kg, in <sup>2</sup> /glass)	120	min	FTM 8
Tack (quick stick stainless steel)	1.2	N	FTM 9
Min Application Temperature	+5	°C	
Service Temperature	-20 to +80	°C	

**Type:** Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surface.

Liner	Target	Unit	Method
Basis weight	62 ± 3	g/m <sup>2</sup>	ISO 536
Thickness	52 ± 4	μ	ISO 534

**Description:** Super-calendered yellow translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

### Application and use

High resolution standard gloss label for multicolour printing. Extensively used in food and beverage industry, logistics, stationery, and cosmetics products.

### Converting and Printing

Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

### Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

### Shelf Life and Storage Conditions

1 year when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: CO ACRY REM / 26GY / 876RA

Date: 10/02/16

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.