

ROLL LABEL - POLYPROPYLENES

Issue date : 11/03/2008  
Date last modification : 10/04/2012**05317 RI-757/60 PP GLOSS WHITE CAVITATED TC AR801 WG62****Face Material**

Gloss white top coated cavitated polypropylene.

Type	Top coated cavitated polypropylene	
Colour and Finish	Gloss white	
Weight	45 g/m <sup>2</sup> ±10%	ISO-536
Thickness	60 µ ±10%	ISO 534-80

**Adhesive**

Acrylic removable adhesive featuring good clarity and clean removability from glass, laminated plastics and crosslinked enamels. Not suitable for application on papers, PVC and air dried paints and varnishes.

Reference	AR801	
Type	Acrylic removable	
Min. Appl. Temp.	+5 °C	
Service Temp.	-40 °C/+120 °C	
Shear	High	
Tack	2 N/25mm	FINAT FTM9
Final Adhesion	2 N/25mm	FINAT FTM2

This adhesive complies with FDA 175.105.

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m <sup>2</sup> ±10%	ISO 536
Thickness	55 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

**Applications**

Suitable for high quality labels, that must be removed after a period of time.  
Not recommended for fan folder tags.

**Printing Methods**

Printable with UV letterpress, UV screenprinting, UV flexo, gravure and hot stamping.  
Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
All information is subject to change without prior notice.

