

Roll Label - PolyestersIssue date : 26/03/2009
Date last modification : 03/02/2011**00591 RI-COTE 49 PET MATT SILVER AP900 WG90****Face Material**

Matt silver metallized polyester.

Type	Polyester	
Colour and Finish	Matt silver	
Weight	70 g/m ² ±10%	ISO 536
Thickness	50 µ ±10%	ISO 534

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP900	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-30°C/+120°C	
Shear	Very High	
Tack	6 N/inch ²	FINAT FTM9
Final Adhesion	9 N/inch	FINAT FTM2

This adhesive complies with FDA 175.105.

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	90 g/m ² ±10%	ISO 536
Thickness	77 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Variable information for sequentially numbered labels, bar codes and service information labels on industrial and home equipment.

Printing Methods

Printable with letterpress UV and screenprinting UV. Overprinting systems: dot matrix, typewriters, thermal transfer.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

