Platinum Paper

Product: Coverall Semi Gloss Perm Hot Melt

Face Material	Target	Unit	Method
Substance	85 ± 4	g/m ²	ISO 536
Thickness	69 ± 5	μ	ISO 534

Description: Semi-gloss white coated woodfree paper with high opacity.

Adhesive	Target	Unit	Method
Final Adhesion	9	N/25mm	FTM 2
Shear (1kg, in ² /glass)	Very High	min	FTM 8
Tack (quick stick stainless steel)	16	N/25mm	FTM 9
Min Application Temperature	0	°C	
Service Temperature	-10 to +70	°C	

Type: Rubber based permanent adhesive with high tack and adhesion on difficult and apolar (like PE and PP) substrates. This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV.

Liner	Target	Unit	Method
Basis weight	60 ± 3	g/m²	ISO 536
Thickness	53 ± 3	μ	ISO 534

Description: One side siliconised Yellow Glassine.

Application and use

Blackout/coverall labels.

Converting and Printing

Printable with letterpress UV, flexo UV, offset UV and gravure.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 $^{\circ}$ C \pm 2 $^{\circ}$ C with a relative humidity of 50 %, \pm 5%.

Ref: COV / RP1001 / 05591

Date: 09/12/16

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.