

ROLL LABEL -Issue date : 13/05/2011
Date last modification : 30/08/2012**07602 - RAPIDJET GLOSS COVER INKJET PAPER AP900 + B/O WG62****Face Material**

Gloss white coated woodfree paper.

Type	Coated paper	
Colour and Finish	White	
Weight	85 g/m ² ±10%	ISO-536
Thickness	100 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive with blackout pigmentation, offering strong adhesion to apolar substrates (like PE and PP).

Reference	AP900 + blackout#	
Type	Acrylic permanent	
Min. Appl. Temp.	+10C	
Service Temp.	-30C +120C	
Shear	Very high	
Tack	6 N/25mm	FINAT FTM9
Final Adhesion	7 N/25mm	FINAT FTM2

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m ² ±10%	ISO 536
Thickness	55 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

Applications

Designed for photo quality printing on inkjet equipment for applications requiring high opacity.

Printing Methods

Printable with Memjet inkjet, other inkjet printing devices plus all standard printing techniques - letterpress UV, flexo UV, offset UV, gravure and thermal transfer with selected ribbons.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

