

Platinum Paper

Product: Laser G Water Removable WK55

Face Material	Target	Unit	Method
Substance	70 ± 4	g/m ²	ISO 536
Thickness	90 ± 5	μ	ISO 534

Description: Uncoated woodfree paper guaranteed for laser printing.

Adhesive	Target	Unit	Method
Peel Adhesion (peel 180° 20'/stainless steel)	12	n/25mm	FTM 1
Peel Adhesion (peel 180° 24h/kraft)	5	n/25mm	FTM 1
Peel Adhesion (peel 180° 24h/PE)	4	n/25mm	FTM 1
Shear (1kg, in ² /glass)	60	min	FTM 8
Tack (quick stick stainless steel)	7	N	FTM 9
Min Application Temperature	-35	°C	
Service Temperature	-40 to +60	°C	

Type: Water removable adhesive with high cohesion and medium adhesion and tack. Ideal for labelling different types of reusable transport boxes and trays in logistics and other surfaces used in retail such as glass, ceramic, plastic.

Liner	Target	Unit	Method
Basis weight	55 ± 3	g/m ²	ISO 536
Thickness	56 ± 4	μ	ISO 534

Description: White liner guaranteed for laser printing. For the conversion of reels to sheets.

Application and use

Suitable for laser, and inkjet printing and photocopying machines.

Converting and Printing

Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, and laser.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: LAS WR / 55LK / 432AS

Date: 18/07/18

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.