

ROLL LABEL - RAPID JET

Issue date : 27/06/2013
Date last modification : 13/12/2016**4-RL1B-07979 RAPIDJET MATT INKJET PAPER AP904 WG62****Face Material**

Matt white coated woodfree paper.

Type	Coated paper	
Colour and Finish	White	
Weight	87 g/m ² ±10%	ISO-536
Thickness	108 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive on with strong adhesion to apolar substrates (like PE and PP).

Reference	AP 904	
Type	Acrylic permanent	
Min. Appl. Temp.	+ 5 °C	
Service Temp.	-40 °C / + 100°C	
Shear	Medium	
Tack	13 N/25mm	FINAT FTM9
Final Adhesion	11 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m ² ±10%	PP-032 - ISO 536
Thickness	54 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

Applications

Designed for photo quality printing on inkjet equipment, for small or medium label volumes.

Printing Methods

Memjet, Primera and water-based inkjet technology printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

