

Platinum Paper

Product: Thermal Transfer Perm Acrylic

Face Material	Target	Unit	Method
Substance	80 ± 10%	g/m ²	ISO 536
Thickness	65 ± 10%	μ	ISO 534

Description: White woodfree super calendared paper.

Adhesive	Target	Unit	Method
Final Adhesion	11	N/25mm	FTM 2
Shear (1kg, in ² /glass)	Medium	min	FTM 8
Tack (quick stick stainless steel)	13	N/25mm	FTM 9
Min Application Temperature	5	°C	
Service Temperature	-40 to +100	°C	

Type: Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP). This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner	Target	Unit	Method
Basis weight	58 ± 3	g/m ²	ISO 536
Thickness	51 ± 4	μ	ISO 534

Description: One side siliconised Yellow Glassine.

Application and use

Bar codes and identification labels.

Converting and Printing

Printable with thermal transfer and with letterpress UV and flexo UV.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: TR / AP904 / 01959

Date: 11/12/18

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.