

Platinum Paper

03147 RI-707/60 PP Gloss Clear TC /AP901/WG62

Face Material	Target	Unit	Method
Substance	54 ± 10%	g/m ²	ISO 536
Thickness	60 ± 10%	μ	ISO 534

Description: Gloss clear top coated polypropylene.

Adhesive	Target	Unit	Method
Final Adhesion	7	n/25mm	FTM 2
Shear (1kg, in ² /glass)	High	min	FTM 8
Tack (quick stick stainless steel)	8	n/25mm	FTM 9
Min Application Temperature	-5	°C	
Service Temperature	-40 to +120	°C	

Type: Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

This adhesive is approved by ISEGA (Direct contact dry & moist, non-fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner	Target	Unit	Method
Basis weight	62 ± 10%	g/m ²	ISO 536
Thickness	55 ± 10%	μ	ISO 534
Transparency	>45	%	DIN 53 147-64

Description: One sided siliconised White Glassine

Application and use

Prime labels for body care products, household chemicals, appliances, and toys. Not recommended for fan folder tags.

Converting and Printing

Printable with letterpress UV, screen-printing UV and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: 03147 RI-707/60 PP Gloss Clear TC AP901 WG62

Date: 22/12/2011

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.