

Platinum Paper

Product: UD PVC Security Matt White 70/SZ

Face Material	Target	Unit	Method
Substance	135 ± 4	g/m ²	ISO 536
Thickness	70 ± 5	μ	ISO 534

Description: Ultra Destructible. White semi-glossy PVC film with low resistance to tearing.

Adhesive	Target	Unit	Method
Coat Weight	17 ± 2	g/m ²	FMT 12
Peel adhesion (180°) 20 min	n.d*	N/25mm	FTM 1
Peel adhesion (180°) 24 h	n.d*	N/25mm	FTM 1
Shear (1kg, in ² /glass)	>80	hrs	FTM 8
Tack (quick stick stainless steel)	n.d*	N/25mm	FTM 9
Min Application Temperature	+5	°C	
Service Temperature	-5 to +40	°C	

* value not determinable.

Type: Solvent-based permanent acrylic adhesive with high adhesion and high cohesion.

Liner	Target	Unit	Method
Basis weight	80 ± 3	g/m ²	ISO 536
Thickness	70 ± 3	μ	ISO 534
Release	15± 5	g/25mm	FTM 3

Description: Super calendared, high density backing paper 80 gr/sqm. Constant thickness, good mechanical properties, suitable for automatic labelling. Good quality for optical scanning.

Application and use

Specific product suitable for security labels. It's extremely fragile face material tends to break when trying to remove the label.

Converting and Printing

Printable with letterpress UV, flexo UV, offset UV and gravure and Thermal transfer.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: UD PVC Security White Matt 70/SZ/80 / CR 010751

Date: 04/03/2018

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.