

# Platinum Paper

## Product: PP50 Clear Perm Acrylic on Clear 30 PET

Face Material	Target	Unit	Method
Thickness	50 ± 10%	μ	ISO 534

**Description:** Biaxial oriented polypropylene film, transparent gloss, cavitated. With topcoat

Adhesive	Target	Unit	Method
Peel Adhesion (24h on glass)	14 ± 6	N/25mm	FTM 1
Min Application Temperature	+5	°C	
Service Temperature	-30 to +90	°C	

**Type:** Copolymeric acrylates, extra high shear strength, solvent free, excellent resistance to UV-light and ageing, complies with EN 71/3 (application on toys) and European packaging directive 94/62/EC (heavy metals). All adhesives are approved for application on dry and moist, non-fatty food (ISEGA certificate)..

Liner	Target	Unit	Method
Basis weight	42 ± 3	g/m <sup>2</sup>	ISO 536
Thickness	30 ± 4	μ	ISO 534

**Description:** PET-foil, high tensile strength, excellent die-cutting properties, solvent based siliconization, qualified for High Speed-Labeling

---

**Application and use** Decorative labels for cosmetics, food, chemistry etc..

**Converting and Printing** Suitable for printing on flexo (all types), offset, letterpress, gravure, screen printing, hot and cold foil stamping

### Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

### Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Date: 10/06/2021

---

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.