

Platinum Paper

Product: Sand textured Matt 38 μ PP Wet Laminate.

Properties	Unit	Values
Thickness	μ	38
Average Yield	m ² /kg	53.76
Gloss	%	12
Wetting Tension	Dynes/cm	\geq 38
Max roughness profile	μ	13-30
Temperature Range	^o C	-50 - +130

Description: Polypropylene transparent wet lamination Matt film, corona treated on both sides. Film has a sandy/gritty texture. Low melt adhesive coating inside.

Application and use

Ideal for beverage, food and cosmetic decorative labels.

Converting and Printing

Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, laser, hot stamping. Applied using inline adhesive application.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 $^{\circ}$ C \pm 2 $^{\circ}$ C with a relative humidity of 50 %, \pm 5%.

Ref: Gloss PP 38 μ / Corona treated 2 sides/ Sand texture

Date: 03/09/21

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.