

Platinum Paper

Product: Gloss 50 μ Polypropylene Overlamine

Face Material	Target	Unit	Method
Substance	45 \pm 10%	g/m ²	ISO 536
Thickness	50 \pm 10%	μ	ISO 534

Description: Gloss clear top coated polypropylene.

Adhesive	Target	Unit	Method
Final Adhesion	7	N/25mm	FTM 2
Shear (1kg, in ² /glass)	High	min	FTM 8
Tack	8	N/25mm	FTM 9
Min Application Temperature	-5	°C	
Service Temperature	-40 to +120	°C	

Type: Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner	Target	Unit	Method
Basis weight	62 \pm 10%	g/m ²	ISO 536
Thickness	54 \pm 10%	μ	ISO 534
Transparency	>45	%	DIN 53 147-64

Description: One side siliconised White Glassine

Application and use

Labels on rigid or semi-rigid polyethylene and polypropylene containers. Top coating and adhesive are fully compliant with food industry requirements.

Not recommended for fan folder tags.

Converting and Printing

Printable with flexo UV, offset UV, letterpress UV, screen printing UV, gravure and hot stamping.

It is recommended to over varnish in order to improve the scratch and chemical resistance of the finished label.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C \pm 2 °C with a relative humidity of 50 %, \pm 5%.

Ref: Gloss PP 50 / AP901 / 02518

Date: 9/12/16

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.