

## Product: Gloss Jet Paper Perm Acrylic

Face Material	Target	Unit	Method
Substance	85± 10%	g/m <sup>2</sup>	ISO 536
Thickness	100 ± 10%	μ	ISO 534

**Description:** Gloss white coated woodfree paper

Adhesive	Target	Unit	Method
Final Adhesion	11	n/25mm	FTM 2
Tack	13	N/25mm	FTM 9
Shear	medium		
Min Application Temperature	+5	°C	
Service Temperature	-40 to +100	°C	

**Type:** Acrylic permanent adhesive on with strong adhesion to apolar substrates (like PE and PP).

Liner	Target	Unit	Method
Basis weight	62 ± 10%	g/m <sup>2</sup>	ISO 536
Thickness	54 ± 4%	μ	ISO 534

**Description:** One side white siliconised Glassine

### Application and use

Designed for photo quality printing on inkjet equipment, for small or medium label volumes.

### Converting and Printing

Memjet, Primera and water-based inkjet technology printable. Testing for suitability between media, printers and inks is always recommended prior to use.

### Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

### Shelf Life and Storage Conditions

1 year when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: Gloss Jet Paper AP904/87970

Date: 13/12/16

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.