

Product: Thermal Top G Deep Freeze Hot Melt 3

Face Material	Target	Unit	Method
Substance	70 ± 4	g/m ²	ISO 536
Thickness	66 ± 5	μ	ISO 534

Description: Thermal paper one side coated BP Free. This facestock is made from FSC® certified paper.

Adhesive	Target	Unit	Method
Peel Adhesion (peel 180° 20'/stainless steel)	18	n/25mm	FTM 1
Shear (1kg, in ² /glass)	1300	min	FTM 8
Tack (quick stick stainless steel)	18	N	FTM 9
Min Application Temperature	-5	°C	
Service Temperature	-40 to +60	°C	

Type: Hot-Melt permanent adhesive with high tack and final adhesion, specially designed for use at cold and freeze applications. Ideal for contactless and high speed labelling.

Liner	Target	Unit	Method
Basis weight	62 ± 3	g/m ²	ISO 536
Thickness	52 ± 4	μ	ISO 534

Description: Super-calendered yellow translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Application and use

Recommended for logistics or distribution applications that require high scratch resistance. Also for food application labelling (eg. supermarket scales) in environments without humidity, oils or plasticizers.

Converting and Printing

Suitable for printing on UV flexo, offset UV, letterpress (conventional and UV).

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

1 year when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: THERMAL TOP BP FREE / 26GY / 003MH

Date: 1/1/22

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.