

Product: Triplex Vellum Hot Melt

Face Material	Target	Unit	Method
Substance	70	g/m ²	ISO 536
Thickness	88	μ	ISO 534

Description: Triplex construction. White calendered woodfree paper.

Adhesive	Target	Unit	Method
Final Adhesion	9	N/25mm	FTM 2
Tack (Glass)	14	N	FTM 9
Min Application Temperature	0	°C	
Service Temperature	-40 to +60	°C	

Type: Super permanent rubber based hot melt adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP).

Liner	Target	Unit	Method
Type	Yellow one side siliconized glassine paper		
Basis weight	54	g/m ²	ISO 536
Thickness	46	μ	ISO 534
Type	White one side siliconized glassine paper		
Basis weight	58	g/m ²	ISO 536
Thickness	51	μ	ISO 534

Application and use

Office and administrative document labels.

Converting and Printing

Printable with flexo UV, letterpress UV, offset UV and thermal transfer with selected ribbons.

Packaging

The rolls are slit according to customer requirements. They are delivered on pallets or in cartons. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

2 years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 20 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Ref: VEL TRIPLEX/ACRYLIC/W/Y

Date: 17/05/24

All products supplied by Platinum Paper Limited are subject to the manufacturers strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable but does not constitute a warranty. Because of the variety of uses of Platinum Paper products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.